

MATERIAL SAFETY DATA SHEET

MANUFACTURER'S NAME
Sudbury Boat Care Products
65 Walnut Street
Peabody, MA 01960

For Emergencies Call Chemtrec: (800)424-9300
Information Telephone Number: (978)532-4019

HMIS: H1, F2,R1

Date of Preparation:

February 7, 2001, Revised 4/14/2009

SECTION I - PRODUCT INFORMATION

<u>PRODUCT NUMBER</u>	<u>PRODUCT NAME</u>	<u>PRODUCT CLASS</u>
300, 320, 301, 321, 302, 322	Elastomeric Sealant	Marine Sealant

SECTION II - HAZARDOUS INGREDIENTS

<u>INGREDIENT</u>	<u>CAS#</u>	<u>% BY WT</u>	<u>EXPOSURE LIMITS</u>	<u>VAPOR PRESSURE</u>
Toluene *	108-88-3	34	100 PPM	22 mm Hg

* Reportable under SARA Title III Section 313

Toluene is listed under California Proposition 65 as a chemical that is known to the State of California to cause birth defects or other reproductive harm.

SECTION III - PHYSICAL DATA

Boiling Point: 232 °F Vapor Density: Heavier Than Air Evaporation Rate: (n-butyl acetate=1): 2.00
Solids (VOL.): 64% Density: 7.76 lb./gal. Sp. Gr.: 0.93

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flammability Classification: Flammable Liquid Flash Point (PCC): 50 °F
Explosive Limits in Air: Lower - 1.2% Upper - 7.2%
Extinguishing Media: Regular Foam, Carbon Dioxide, or Dry Chemical
Unusual Fire or Explosion Hazards: None Special Fire Fighting Procedures: None

SECTION V - HEALTH HAZARD DATA

Eye: Severe Irritant Skin: Irritant Inhalation: Excessive inhalation of vapors can cause nasal and respiratory irritation, central nervous system depression, dizziness, weakness, fatigue, nausea, and headache.
Ingestion: Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

First Aid:

Eyes: Flush immediately with large amounts of water for at least 15 minutes. Get medical attention.
Skin: Wash thoroughly with soap and water. Wash contaminated clothing before reuse. If irritation develops and persists, see a physician. Inhalation: If you experience difficulty in breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. Ingestion: DO NOT INDUCE VOMITING, get medical attention immediately.

Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

SECTION VI - REACTIVITY DATA

Stability: Stable Hazardous Polymerization: Will not occur Materials to Avoid: Strong oxidizers
Hazardous Decomposition Products: Usual products of combustion when burned.

SECTION VII - SPILL AND LEAK PROCEDURES

Shovel into containers for disposal.

SECTION VIII - SAFE HANDLING AND USE

Use with adequate ventilation. Keep away from heat and open flame. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C) or leave area. Avoid contact with skin.

SECTION IX - STORAGE AND DISPOSAL

Discarded material is a hazardous waste. Dispose of according to all federal, state, and local regulations. Store in a manner that will avoid damage to the container. Store away from sources of heat.