

SECTION 1 – IDENTIFICATION

Manufacturer:

Company: Sudbury Boat Care **Emergency Contact Information** Call CHEMTREC 800-424-9300

Street Address: 65 Walnut Street City / State / Zip: Peabody, MA 01960

Phone: (978) 532-4019

Product Name: Marine Sealant

> Sealant (color designation) Marine, Sealant Clear Marine, Synonyms:

Sealant Elastomeric (color designation), Sealant Clear Liquid Penetrating

Part Number(s): 300, 301, 302, 305, 308, 309, 310, 350 Recommended use: Adhesive for marine applications Restrictions on use: Use only as recommended

SECTION 2 – HAZARD(S) IDENTIFICATION

This material is considered hazardous per the US OSHA Hazard Communication Standard (29CFR1910.1200).

Skin corrosion/irritation, Category 2

Serious eye damage/eye irritation, Category 2A

Reproductive Toxicity, Category 2 Hazard

Specific Target Organ Toxicity – Single Exposure, Category 3 (narcotic effects) Classification:

Specific Target Organ Toxicity – Repeated/Prolonged Exposure, Category 2 (auditory system, eyes; inhalation)

Flammable Liquids, Category 2

Signal Word: Danger

> Causes skin irritation. Causes serious eye irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs (auditory

Hazard Statements: system, eyes) through prolonged or repeated exposure (inhalation). Highly flammable liquid

and vapor.

Hazard Symbols:







Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear eye and face protection, protective gloves and clothing. Do not breathe fumes or vapors. Use only outdoors or in a well-ventilated area. Wash hands and exposed skin thoroughly after handling. Keep away from heat, hot surfaces, sparks and open flames. - No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

RESPONSE

Precautionary Statements:

If on skin (or hair): Take off immediately all contaminated clothing. Wash with soap and plenty of water.

If skin irritation occurs: Get medical attention.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call an

ambulance or poison center if you feel unwell.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If exposed or concerned: Get medical advice.

Get medical advice if you feel unwell. Take off contaminated clothing and wash it before

In case of fire: Use alcohol-resistant foam, carbon dioxide, dry chemical powder, or sand to extinguish.

SDS: Marine Sealant (300 Series) Revision Date: 14 December 2021 Page 1 of 6



STORAGE

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

DISPOSAL

Contact local municipal, state and/or federal agencies to determine appropriate disposal options for the product. Dispose of this container with a registered reconditioner or as otherwise appropriate.

Hazards Not

Otherwise Classified:

None.

General Advice: Practice good general industrial hygiene.

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Nature of product: Mixture

Ingredient Name	CAS Number	%	Type	GHS Classification
Toluene	108-88-3	30-60	A	Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2A Reproductive toxicity, Category 2 Specific target organ toxicity - single exposure, Category 3 (narcotic effects) Specific target organ toxicity - repeated exposure (Inhalation), Category 2 (Auditory system, Eyes) Aspiration hazard, Category 1 Flammable liquids, Category 2

Type: [A] Consituent [B] Surplus Original Reactant [C] Side Product [D] Degradation Product [E] Impurity If Chemical Name & CAS # is "proprietary" &/ Weight-% is listed as a range: the specific chemical identity and/or percentage of composition has been withheld as a trade secret or percentage of composition is due to batch variation.

There are no additional ingredients present which, to the best knowledge of the manufacturer, are classified and contribute to the classification of the substance and therefore require reporting.

SECTION 4 - FIRST-AID MEASURES

Provide this SDS to any medical personnel responding to a call for help. General Advice:

The product exhibits adhesive properties.

Rinse immediately with plenty of water, including under the eyelids, for at least Eye contact:

15 minutes. Get medical attention.

Wash off immediately with plenty of soap and water for at least 15 minutes. Skin contact:

Remove contaminated clothing.

Remove patient to fresh air. If breathing is difficult, keep patient at rest, in a

position comfortable for breathing. When administering rescue breathing, Inhalation:

rescuer must take precautions against exposure.

Do NOT induce vomiting. Rinse mouth. Give a conscious patient water to drink. Ingestion:

Never give anything by mouth to an unconscious patient. If the patient continues

to feel unwell, get medical attention.

Most Important Symptoms, Acute & Delayed:

Irritation of the affected area.

Indication of immediate medical attention or special treatment:

No data available

Treat symptomatically. The adhesive properties of the product may necessitate Note to Physician:

mechanical removal from the eye.

SDS: Marine Sealant (300 Series) Revision Date: 14 December 2021 Page 2 of 6



SECTION 5 - FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: Foam, carbon dioxide, dry chemical powder, sand.

Unsuitable Extinguishing Media: Water may spread burning material.

Heating may generate explosive vapor/air mixtures. Combustion may result in hazardous combustion products including Carbon monoxide, and Carbon

Specific hazards: dioxide. Do not allow run-off from firefighting to enter drains or water

courses.

Special precautions for fire-fighters:

Do not breathe fumes. Use water to cool surrounding containers. Treat as

an oil fire. Wear SCBA if fighting fire close-in.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, & emergency procedures:

Ensure adequate ventilation. Exclude unnecessary personnel. Eliminate all ignition sources. Use non-sparking tools. Prevent discharge to the ground, sewers, drains, or waterways. Wear Personal Protective

Equipment (PPE) appropriate to clean-up.

Methods and materials for containment and clean-up:

Prevent entry into waterways, sewer, basements, or confined areas. Dike material to prevent spreading. Use non-sparking tools. Prevent further leakage / spillage if safe to do so. Absorb with inert material and transfer to a waste container. Clean small spills with absorbent cloth, and wash

surface to remove residual contamination.

General advice:

Spilled material may cause slippery conditions. Prevent further leakage or spillage if safe to do so. Discharge into the environment should be avoided. Inform authorities of all environmental releases as appropriate.

SECTION 7 - HANDLING AND STORAGE

Observe good general industrial hygiene. Avoid contact with skin and eyes. Avoid prolonged exposure. Do not breathe mist or vapor. Keep container closed when not in use. Do not eat, drink, or use tobacco products when

Precautions for safe handling: using this product. Ensure adequate ventilation. Wear appropriate

personal protective equipment. Do not use pressure to empty drums. Keep

away from open flames, hot surfaces, and sources of ignition. Wash

thoroughly after handling. Avoid release to the environment.

Conditions for safe storage: `

Store locked up. Keep containers tightly closed, out of direct sunlight, at

ambient temperatures in a dry and well-ventilated place.

Materials incompatible with product:

Strong oxidizing agents.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Substance Identity	CAS#	Regulating Body	Value Type	Value
Toluene	108-88-3	OSHA Z-2	PEL as TWA	200 ppm

Maintain adequate ventilation (10 air changes / hour minimum). Use general ventilation, local exhaust, and other necessary engineering controls to control

Engineering Controls: airborne levels below exposure limit. Avoid heat and sparks (from grinding or

static discharge). Ensure eyewash stations and showers are available and in

good working order.

Use good general industrial hygiene. Use personal protective equipment. If

Individual protection measures: local exhaust is inadequate, use an appropriate respirator. Do not eat, drink, or

use tobacco products when working with this product.

SDS: Marine Sealant (300 Series) Revision Date: 14 December 2021 Page 3 of 6



SECTION 9 - PHYSICAL & CHEMICAL PROPERTIES

OLOTION 3 - I ITTOICAL & CITEMICAL I NOT ENTILE								
Appearance:	A thick, extrudable semi- solid. The color of the product (or lack thereof) matches the designation in the product name.	Lower flammability (or explosive) limits:	No data available					
Odor: Toluene		Upper flammability (or explosive) limits:	No data available					
Odor threshold:	No data available	Vapor Pressure:	No data available					
pH:	Not applicable	Vapor Density:	No data available					
Melting / Freezing Point:	No data available	Relative Density:	0.8					
Initial Boiling Point:	No data available	Solubility:	Insoluble in water					
Boiling Range:	No data available	Partition Coefficient: n-Octane / Water	No data available					
Flash Point:	50 °F (10 °C)	Auto-ignition Temperature:	No data available					
Evaporation Rate:	No data available	Decomposition Temperature:	No data available					
Flammability (solid, gas):	Not applicable	Viscosity:	No data available					

NOTE: the physical data presented above are typical values and should not be construed as a specification.

SECTION 10 - STABILITY & REACTIVITY

Reactivity: Not reactive under typical conditions.

Chemical stability: Stable under typical storage conditions.

Possibility of hazardous reactions: Will not polymerize.

Conditions to avoid: Exceptionally high temperatures, ignition sources, poorly ventilated working

or storage areas.

Incompatible materials: Strong oxidizing agents.

Hazardous decomposition products: Will not decompose under typical conditions.

SECTION 11 - TOXICOLOGICAL INFORMATION

Skin contact and eye contact are the most likely routes of exposure.

Likely routes of exposure: Exposure by ingestion is possible but unlikely.

Given the nature of the product, exposure by inhalation or injection is unlikely.

Will adhere to the skin. May cause skin irritation. Causes serious eye irritation.

Symptoms and effects: Inhalation of vapors may cause narcotic effects. Symptoms of overexposure

include headache, dizziness, tiredness, nausea and vomiting.

Chronic effects: Suspected of damaging fertility or the unborn child. May cause damage to organs

through prolonged or repeated exposure.

Numerical measure of toxicity: This product is not classified as Acutely toxic.

Neither this product, nor those components with applicable routes of exposure

Carcinogenicity: present in concentrations of ≥ 0.1%, appear on the NTP list, the IARC list, or the

OSHA list of known or potential carcinogens.

SECTION 12 – ECOLOGICAL INFORMATION

Aquatic toxicity: No data available

Terrestrial toxicity: No data available

Persistence and degradability: No data available

Bioaccumulative potential: No data available

Mobility in soil: No data available

Other adverse effects: No data available

SDS: Marine Sealant (300 Series) Revision Date: 14 December 2021 Page 4 of 6



SECTION 13 – DISPOSAL CONSIDERATIONS

Disposal method: Dispose of unused and/or contaminated material in accordance with local, state,

and federal regulations.

Container disposal method:

Send durable containers to a reconditioner for refurbishment. Dispose of other

containers in accordance with local, state, and federal regulations.

SECTION 14 – TRANSPORTATION INFORMATION

UN1133, Adhesives, 3, II

US DOT Highway & Rail: This product qualifies for the exceptions given at 49CFR173.150.

This product is NOT REGULATED in Limited Quantities.

Marine Pollutant: No data available

IMO / IMDG Water Transport: No data available

Transport in bulk according to Annex I or II Consult IMO regulations before transporting in bulk by ocean

of MARPOL 73/78 and the IBC / IGC Code: transport.

ICAO / IATA Air Transport: No data available

SECTION 15 – REGULATORY INFORMATION

Chemical Inventory Compliance

This product complies with the national inventories of the following countries:

OSHA Hazard Communication Standard

(as regulated by US 29CFR1910.1200):

CERCLA This product, as supplied, contains the following hazardous substances with a Comprehensive Environmental Response Compensation and Liability Act Reportable Quantity (CERCLA RQ) as regulated by US 40CFR302 (a release equal to or greater than the RQ requires reporting to the National Response Center (800-424-8802), the SERC, and the LEPC):

EPCRA Sections 301-303 & 304 This product, as supplied, contains the following Extremely Hazardous Substances (EHS) subject to a Threshold Planning Quantity (TPQ) and Reportable Quantity (RQ) as regulated by US 40CFR355 (a release equal to or greater than the RQ requires reporting to the SERC and LEPC):

EPCRA Section 311 & 312

(as regulated by US 40CFR370 for Tier II Reporting):

EPCRA Section 313

(as regulated by US 40CFR372 for TRI Reporting): **US CWA** This product, as supplied, contains the following substances regulated as pollutants pursuant to the Clean Water Act (40CFR122.21 & 40CFR122.22):

US CAA HAPs This product, as supplied, contains the following substances regulated as Hazardous Air Pollutants under the Clean Air Act Section 112:

US TSCA

This material is considered hazardous by the OSHA HazCom 2012 Standard (29CFR1910.1200).

Calculated RQ exceeds reasonably attainable upper limit.

None.

Refer to Sections 2 and 3 of this SDS for information.

No components listed above de minimus threshold concentrations.

No Data Available.

No Data Available.

SDS: Marine Sealant (300 Series) Revision Date: 14 December 2021 Page 5 of 6



SECTION 16 - OTHER INFORMATION

Revision Date: 14 December 2021

NFPA Rating: Health / Blue: Flammability / 3 Instability / Yellow: Specific Hazard / Specific Hazard /

This material is usually prepared and distributed as a consumer product. Consumer use should follow precautions and instructions found on the consumer package. This SDS is intended for communicating hazards in the workplace.

Disclaimer: This Safety Data Sheet (SDS) was prepared to comply with the US OHSA Hazard Communication Standard (29 CFR 1910.1200; aka HazCom 2012). This SDS supersedes any previous SDS. The information and recommendations described in this SDS are provided in good faith and based upon data believed to be correct. However, the information provided in this SDS is provided without any warranty, express or implied, regarding its correctness or accuracy. The information provided applies only to the product as shipped. The information is offered for the end user's information, consideration, and further investigation. The information contained in this document is not to be construed as absolute or complete since additional information may be necessary or desirable when particular / exceptional conditions / circumstances exist; or, because of applicable laws or government regulations. Since the actual conditions for the use of the product are beyond the manufacturer's control, no guarantee (express or implied) is made as to the effects of such use or the results to be obtained. The sole responsibility to determine appropriate conditions for the use of this product and the assumption of liability for any loss, damage, or expense arising from the product's use rests with the end user. The end user is encouraged to read the SDS and understand any associated hazards associated with the product thoroughly before using. It is the end user's responsibility to ensure that use, handling, storage, and disposal of the product complies with all federal, state, provincial, and local laws.

SDS: Marine Sealant (300 Series) Revision Date: 14 December 2021 Page 6 of 6