



#### SECTION 1 - IDENTIFICATION

**Manufacturer:** Sudbury Boat Care

Company: Tip Top Products

**Street Address:** 65 Walnut Street **City / State / Zip:** Peabody, MA 01960

**Phone:** (978) 532-4019

Product Name: Wood Oil Sealer

**Synonyms:** Tip Top Teak® Wood-Oil Sealer

Part Number(s): TTT-TS1001-Q, TTT-TS1001-BT4, TTT-TS1002-G, TTT-TS1002-LB-1,

Recommended use: Wood sealer

Restrictions on use: Use only as recommended

### **SECTION 2 – HAZARD(S) IDENTIFICATION**

This material is considered hazardous per the US OSHA Hazard Communication Standard (29CFR1910.1200).

Aspiration Hazard: Category 1

Hazard Classification: Carcinogenicity: Category 1B

Flammable Liquids: Category 3

Signal Word: Danger

Hazard Statements: May be fatal if swallowed and enters airways. May cause cancer.

Flammable liquid and vapor.

### **Hazard Symbols:**





#### **PREVENTION**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear eye and face protection, protective gloves and clothing. Keep away from heat, sparks and open flames. - No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

**Emergency Contact Information** 

Call CHEMTREC 800-424-9300

### RESPONSE

**If swallowed:** Immediately call an ambulance or poison center. Do NOT induce vomiting.

### **Precautionary Statements:**

If exposed or concerned: Get medical advice/attention.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with plenty of water under shower.

In case of fire: Use alcohol-resistant foam, carbon dioxide, dry chemical

powder, or sand to extinguish.

### STORAGE

Store locked up. Store in a well-ventilated place. Keep cool.

#### **DISPOSAL**

Contact local municipal, state and/or federal agencies to determine

appropriate disposal options for the product. Dispose of this container with a

registered reconditioner or as otherwise appropriate.

**Hazards Not Otherwise Classified:** 

None.

General Advice: Practice good general industrial hygiene.

SDS: Wood Oil Sealer Revision Date: 29 June 2021 Page 1 of 6





### SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Nature of product: Mixture

Ingredient Name	CAS Number	%	Type	GHS Classification	
Distillates (petroleum), hydrotreated light	64742-47-8	60-80	А	Flammable liquids: Category 3 Aspiration Hazard: Category 1	
Kerosine (petroleum)	8008-20-6	5-10	А	Flammable liquid: Category 3 Acute Toxicity: Oral, Category 4 Acute Toxicity: Inhalation, Category 2 Skin Irritation: Category 2 Eye Irritation: Category 2B Carcinogenicity: Category 1B STOT-SE: Category 3 Aspiration Hazard: Category 1	

Type: [A] Consituent [B] Surplus Original Reactant [C] Side Product [D] Degradation Product [E] Impurity If Chemical Name & CAS # is "proprietary" &/ Weight-% is listed as a range: the specific chemical identity and/or percentage of composition has been withheld as a trade secret or percentage of composition is due to batch variation. There are no additional ingredients present which, to the best knowledge of the manufacturer, are classified and contribute to the classification of the substance and therefore require reporting.

### **SECTION 4 – FIRST-AID MEASURES**

**General Advice:** Provide this SDS to any medical personnel responding to a call for help.

Rinse immediately with plenty of water, including under the eyelids, for at least Eye contact:

15 minutes. Get medical attention.

Wash off immediately with plenty of soap and water for at least 15 minutes. Skin contact:

Remove contaminated clothing.

Remove patient to fresh air. If breathing is difficult, keep patient at rest, in a Inhalation:

position comfortable for breathing. When administering rescue breathing,

rescuer must take precautions against exposure.

Do NOT induce vomiting. Rinse mouth. Give a conscious patient water to drink.

Never give anything by mouth to an unconscious patient. Call a Poison Center Ingestion:

or transport to a hospital without delay.

**Most Important Symptoms,** 

Acute & Delayed:

Indication of immediate medical

attention or special treatment:

Irritation of the affected area.

No data available

Note to Physician: Treat symptomatically.

### SECTION 5 - FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: Water fog, foam, carbon dioxide, dry chemical powder, sand.

**Unsuitable Extinguishing Media:** High-pressure water jet, water, water spray/

Heating may generate explosive vapor/air mixtures. Combustion may result

in hazardous combustion products including Carbon monoxide, and Carbon Specific hazards:

dioxide. Do not allow run-off from firefighting to enter drains or water

Do not breathe fumes. Use water to cool surrounding containers. Treat as Special precautions for fire-fighters:

an oil fire. Wear SCBA if fighting fire close-in.

SDS: Wood Oil Sealer Revision Date: 29 June 2021 Page 2 of 6





#### SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, & emergency procedures:

Ensure adequate ventilation. Exclude unnecessary personnel. Eliminate all ignition sources. Prevent discharge to the ground, sewers, drains, or waterways. Wear Personal Protective Equipment (PPE) appropriate to

clean-up.

Methods and materials for containment and clean-up:

Prevent entry into waterways, sewer, basements, or confined areas. Dike material to prevent spreading. Prevent further leakage / spillage if safe to do so. Absorb with inert material and transfer to a waste container. Clean small spills with absorbent cloth, and wash surface to remove

residual contamination.

Spilled material may cause slippery conditions. Prevent further leakage General advice:

or spillage if safe to do so. Discharge into the environment should be avoided. Inform authorities of all environmental releases as appropriate.

### SECTION 7 - HANDLING AND STORAGE

Observe good general industrial hygiene. Avoid contact with skin and eyes. Avoid prolonged exposure. Do not breathe mist or vapor. Keep container closed when not in use. Do not eat, drink, or use tobacco products when

Precautions for safe handling:

using this product. Ensure adequate ventilation. Wear appropriate personal protective equipment. Do not use pressure to empty drums. Keep away from open flames, hot surfaces, and sources of ignition. Wash

thoroughly after handling. Avoid release to the environment.

Conditions for safe storage:

Store locked up. Keep containers tightly closed, out of direct sunlight, at

ambient temperatures in a dry and well-ventilated place.

Materials incompatible with product: Strong oxidizing agents. Strong reducing agents.

### SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Substance Identity	CAS#	Regulating Body	Value Type	Value
Wood Oil Sealer, non-aerosol	Mixture	ACGIH	TLV	200 mg/m <sup>3</sup> or 40 ppm

Maintain adequate ventilation (10 air changes / hour minimum). Use general

ventilation, local exhaust, and other necessary engineering controls to control **Engineering Controls:** airborne levels below exposure limit. Avoid heat and sparks (from grinding or

static discharge). Ensure eyewash stations and showers are available and in

good working order.

Use good general industrial hygiene. Use personal protective equipment. If Individual protection measures:

local exhaust is inadequate, use an appropriate respirator. Do not eat, drink, or

use tobacco products when working with this product.

SDS: Wood Oil Sealer Revision Date: 29 June 2021 Page 3 of 6





### SECTION 9 - PHYSICAL & CHEMICAL PROPERTIES

Appearance:	Yellow, oily liquid	Lower flammability (or explosive) limits:	No data available
Odor:	Solvent odor	Upper flammability (or explosive) limits:	No data available
Odor threshold:	No data available	o data available Vapor Pressure:	
pH:	Not applicable	Vapor Density:	No data available
Melting / Freezing Point:	No data available	Relative Density:	0.9
Initial Boiling Point:	No data available	Solubility:	Insoluble in water
Boiling Range:	No data available	Partition Coefficient: n-Octane / Water	No data available
Flash Point:	105 °F (40.5 °C)	Auto-ignition Temperature:	No data available
Evaporation Rate:	Slow	Decomposition Temperature:	No data available
Flammability (solid, gas):	Not applicable	Viscosity:	No data available

NOTE: the physical data presented above are typical values and should not be construed as a specification.

### SECTION 10 - STABILITY & REACTIVITY

**Reactivity:** Not reactive under typical conditions.

**Chemical stability:** Stable under typical storage conditions.

Possibility of hazardous reactions: Will not polymerize.

Conditions to avoid: Exceptionally high temperatures, ignition sources, poorly ventilated working

or storage areas.

Incompatible materials: Strong oxidizing agents. Strong reducing agents.

Hazardous decomposition products: Will not decompose under typical conditions.

#### SECTION 11 – TOXICOLOGICAL INFORMATION

Skin contact and eye contact are the most likely routes of exposure.

**Likely routes of exposure:** Exposure by ingestion is possible but unlikely.

Given the nature of the product, exposure by inhalation or injection is unlikely.

Symptoms and effects: May cause irritation of the affected area upon contact. May irritate the respiratory tract upon inhalation.

**Chronic effects:** Causes damage to organ through prolonged or repeated exposure.

**Numerical measure of toxicity:** The mixture is not classified as acutely toxic.

Kerosene component of this mixture may contain various proportions of Benzene

Carcinogenicity: (< 0.1%) &/ Naphthalene (1-5%). Benzene appears on the OSHA, NTP, and

IARC lists of known or potential carcinogens. Naphthalene appears on the IARC

list of known or potential carcinogens.

### SECTION 12 - ECOLOGICAL INFORMATION

Aquatic toxicity: No data available

Terrestrial toxicity: No data available
Persistence and degradability: No data available

Bioaccumulative potential: No data available

Mobility in soil: No data available

Other adverse effects: No data available

SDS: Wood Oil Sealer Revision Date: 29 June 2021 Page 4 of 6





#### **SECTION 13 – DISPOSAL CONSIDERATIONS**

**Disposal method:** Dispose of unused and/or contaminated material in accordance with local, state,

and federal regulations.

Container disposal method:

Send durable containers to a reconditioner for refurbishment. Dispose of other

containers in accordance with local, state, and federal regulations.

#### SECTION 14 – TRANSPORTATION INFORMATION

Not Regulated for domestic transportation in quantities less than 119

**US DOT Highway & Rail:** gallons per container.

UN1268, Petroleum distillates, n.o.s., 3, III

Marine Pollutant: No data available

IMO / IMDG Water Transport: No data available

Transport in bulk according to Annex I or II Consult IMO regulations before transporting in bulk by ocean

of MARPOL 73/78 and the IBC / IGC Code: transport.

ICAO / IATA Air Transport: No data available

### **SECTION 15 – REGULATORY INFORMATION**

### **Chemical Inventory Compliance**

This product complies with the national inventories US TSCA of the following countries:

**OSHA Hazard Communication Standard** (as regulated by US 29CFR1910.1200):

CERCLA This product, as supplied, contains the following hazardous substances with a Comprehensive Environmental Response Compensation and Liability Act Reportable Quantity (CERCLA RQ) as regulated by US 40CFR302 (a release equal to or greater than the RQ requires reporting to the National Response Center (800-424-8802), the SERC, and the LEPC):

EPCRA Sections 301-303 & 304 This product, as supplied, contains the following Extremely Hazardous Substances (EHS) subject to a Threshold Planning Quantity (TPQ) and Reportable Quantity (RQ) as regulated by US 40CFR355 (a release equal to or greater than the RQ requires reporting to the SERC and LEPC):

EPCRA Section 311 & 312

(as regulated by US 40CFR370 for Tier II reporting):

**EPCRA Section 313** 

(as regulated by US 40CFR372 for TRI reporting): **US CWA** This product, as supplied, contains the following substances regulated as pollutants pursuant to the Clean Water Act (40CFR122.21 & 40CFR122.22):

**US CAA HAPs** This product, as supplied, contains the following substances regulated as Hazardous Air Pollutants under the Clean Air Act Section 112:

This material is considered hazardous by the OSHA HazCom 2012 Standard (29CFR1910.1200).

None.

None.

Refer to Sections 2 and 3 of this SDS for information.

Naphthalene (CAS #91-20-3): < 0.5%

Linseed oil, cobalt manganese salt (CAS # 68553-15-1): < 2%

No Data Available.

No Data Available.

SDS: Wood Oil Sealer Revision Date: 29 June 2021 Page 5 of 6





State RTK:

**WARNING:** This product can expose you to chemicals including Benzene & Naphthalene, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

## **SECTION 16 – OTHER INFORMATION**

Revision Date: 29 June 2021

NFPA Rating: Health / Blue: Flammability / 2 Instability / Yellow: Specific Hazard / Specific Hazard /

This material is usually prepared and distributed as a consumer product. Consumer use should follow precautions and instructions found on the consumer package. This SDS is intended for communicating hazards in the workplace.

Disclaimer: This Safety Data Sheet (SDS) was prepared to comply with the US OHSA Hazard Communication Standard (29 CFR 1910.1200; aka HazCom 2012). This SDS supersedes any previous SDS. The information and recommendations described in this SDS are provided in good faith and based upon data believed to be correct. However, the information provided in this SDS is provided without any warranty, express or implied, regarding its correctness or accuracy. The information provided applies only to the product as shipped. The information is offered for the end user's information, consideration, and further investigation. The information contained in this document is not to be construed as absolute or complete since additional information may be necessary or desirable when particular / exceptional conditions / circumstances exist; or, because of applicable laws or government regulations. Since the actual conditions for the use of the product are beyond the manufacturer's control, no guarantee (express or implied) is made as to the effects of such use or the results to be obtained. The sole responsibility to determine appropriate conditions for the use of this product and the assumption of liability for any loss, damage, or expense arising from the product's use rests with the end user. The end user is encouraged to read the SDS and understand any associated hazards associated with the product thoroughly before using. It is the end user's responsibility to ensure that use, handling, storage, and disposal of the product complies with all federal, state, provincial, and local laws.

SDS: Wood Oil Sealer Revision Date: 29 June 2021 Page 6 of 6